



产品特性

- ◆ 1*PCIe x16, 1*PCIe x4, 2*PCI
- ◆ Intel® H310芯片组
- ◆ 支持双通道 DDR4 DIMM 至 64GB
- ◆ 1*VGA, 1*DVI-I (DVI-D signal), 1*DP++
- ◆ 2*Intel网口, 10*USB, 6*串口

产品规格

处理器	8/9th Generation Intel® Core™ /Pentium®/Celeron® Processors, LGA 1151 Socket		扩展槽	1*PCIe x16 (Gen 3), 1*PCIe x4 (Gen 2), 2*PCI
系统芯片组	Intel® H310 Chipset			
系统内存	2*288-pin DIMM up to 64GB, Dual Channel DDR4 2400/2666MHz			
BIOS	AMI SPI 128Mbit		显示	1*VGA: resolution up to 1920x1200 @ 60Hz 1*DVI-I (DVI-D signal): resolution up to 1920x1200 @ 60Hz 1*DP++: resolution up to 4096x2304 @ 60Hz
以太网网络	1*Intel® I211AT (10/100/1000Mbps) 1*Intel® I219V (10/100/1000Mbps)			
背部I/O接口	以太网网络	2*GbE (RJ-45)		
	串口	1*RS-232/422/485(RS-232 w/power)(DB-9)		
	USB	4*USB 3.1 (Gen1), 2*USB 2.0		
	PS/2	1*PS/2 (mini-DIN-6)		
内部I/O接口	显示	1*VGA,1*DVI-I (DVI-D signal) ,1*DP++	音频	Realtek ALC888
	音源	1*Line-out, 1*Mic-in, 1*Line-in (opt.)	温度	工作温度: 0 to 60°C, 存储温度: -40 to 85°C without RTC Battery; -30 to 60°C with RTC Battery
	串行端口	1*RS-232/422/485 (RS-232 w/ power) (2.54mm pitch, 4*RS-232)		
	USB	4*USB 2.0(2.54mm pitch)	湿度	工作湿度: 5 to 90% RH, 存储湿度: 5 to 90% RH
	音效	1*S/PDIF, 1*Front Audio Header		
SATA	4*SATA 3.0 (up to 6Gb/s)			
DIO	1*8-bit DIO	尺寸	244mm (9.6")*244mm (9.6")	

订货信息

型号	说明
EB-330-H310-XX	Micro ATX Motherboard supports LGA 1151 Intel® Core™ i7/i5/i3/Pentium, Intel® H310