



产品特性

- ◆ 1*PCIe x16, 1*PCIe x4 , 5*PCI
- ◆ Intel® H310芯片组
- ◆ 支持双通道 DDR4 DIMM 至 64GB
- ◆ 1*VGA, 1*DVI-I (DVI-D 讯号), 1*DP++
- ◆ 2*Intel网口,10*USB, 6*串口

产品规格

处理器	8/9th Generation Intel® Core™ /Pentium®/Celeron® LGA 1151 Socket Processors		扩展槽	1*PCIe x16 (Gen 3), 1*PCIe x4 (Gen 2), 5*PCI
系统芯片组	Intel® H310 Chipset			
系统内存	2*288-pin DIMM up to 64GB, Dual Channel DDR4 2400/2666MHz			
BIOS	AMI SPI 128Mbit		显示	1*VGA: resolution up to 1920x1200 @ 60Hz 1*DVI-I (DVI-D signal): resolution up to 1920x1200 @ 60Hz 1*DP++: resolution up to 4096x2160 @ 60Hz
以太网	1*Intel® I211AT PCIe (10/100/1000Mbps) 1*Intel® I219V Lan Phy (10/100/1000Mbps)			
背部I/O接口	以太网	2*GbE (RJ-45)		
	串口	1*RS-232/422/485 (RS-232w/power)(DB-9)		
	USB	4*USB 3.1 (Gen1), 2*USB 2.0		
	PS/2	1*PS/2 (mini-DIN-6)		
音源	1*Line-out, 1*Mic-in, 1*Line-in (opt., MOQ required)		音频	Realtek ALC888
内部I/O接口	串行端口	1*RS-232/422/485 (RS-232 w/power) (2.54mm pitch) 4*RS-232 (2.54mm pitch)	温度	工作温度: 0 to 60°C 存储温度: -30 to 60°C with RTC Battery; -40 to 85°C without RTC Battery
	USB	4*USB 2.0(2.54mm pitch)	湿度	工作湿度: 5 to 90% RH, 存储湿度: 5 to 90% RH
	音效	1*S/PDIF, 1*Front Audio Header		
	SATA	4*SATA 3.0 (up to 6Gb/s)	尺寸	305mm (12")*244mm (9.6")
	DIO	1*8-bit DIO		

订货信息

型号	说明
EB-630-H310-XX	ATX Motherboard supports LGA1151 Intel® Core™ i7/i5/i3/Pentium, Intel® H310